



Curved Wall Pack MSM1000i

The **Brighter** Look that **Lasts**

Used in parking areas, entrances, walkways, underpasses, loading docks, recreation areas and tunnels.

Design

- Heavy duty two piece die cast aluminum housing is top hinged for ease of maintenance
- Two captive stainless steel door fasteners
- Clear prismatic borosilicate glass reflector is thermal/shock resistant
- Computer designed and precision formed specular aluminum reflector
- Lightweight back plate is easily attached to wall
- UL 1598 listed for wet locations
- Polyester powder finish for excellent impact, corrosion and UV resistance
- Dark Sky friendly



Induction Lighting Benefits

- Long Life – 100,000 hours
- Color rendering – 85 CRI
- Color Temperatures – 3500k, 4100k, 5000k
- Energy Efficient – High Output/Less wattage
- Longer Lumen maintenance – slower degradation
- Consistent color - Minimal color shifting
- Maintenance costs – lasts 15+ years without change out
- Instant On – Can control with photocell and motion sensor
- No flickering. No strobing. No noise
- Operating ambient temperature -30°C (-22°F) ~ +40°C (+104°F)

Specifications/Options

- **Lamp Life:** 100,000 hours
- **Wattage:**

Lamp(System)	Replaces HID
40 (43)	100w
65 (69)	125w
- **Voltages:** 120, 208, 220, 240, 277, (480 special order)
- **Color Temp:** 3500k, 4100k, 5000k
- **Finish:** Bronze, Black, White, or Custom

