



Deluxe Induction High Bay MHB1003i

The **Brighter** Look that **Lasts**

The Deluxe Induction High Bay features an open, acrylic reflector for maximum efficiency in general purpose retail, educational and industrial applications where uplight is required.

Design

- Supplies uplight for uniform lighting of the ceiling, walls and the floor
- Heavy wall, two piece die cast aluminum ballast housing with “Slant 2” mounting geometry for cooler operation and white polyester powder finish for excellent corrosion and impact resistance
- Heavy gauge yoke provides positive mounting of the reflector to the ballast assembly and field adjustable light distribution
- Prismatic reflector is designed for vertical and horizontal lighting and is injection molded with 100% virgin acrylic



Dimension

16.9”L x 10”W x 10.4”D

Induction Lighting Benefits

- Long Life – 100,000 hours
- Color rendering – 85 CRI
- Color Temperatures – 3500k, 4100k, 5000k
- Energy Efficient – High Output/Less wattage
- Longer Lumen maintenance – slower degradation
- Consistent color - Minimal color shifting
- Maintenance costs – lasts 15+ years without change out
- Instant On – Can control with photocell and motion sensor
- No flickering. No strobing. No noise
- Operating ambient temperature -30°C (-22°F) ~ +40°C (+104°F)

Specifications/Options

- **Lamp Life:** 100,000 hours
- **Wattage:**

Lamp(System)	Replaces HID
40 (43)	100w
65 (69)	125w
80 (86)	175w
100 (106)	200w
120 (126)	250w
150 (157)	300w
200 (210)	400w
250 (262)	500w
280 (286)	750w
400 (420)	1000w
- **Voltages:** 120, 208, 220, 240, 277, (480 special order)
- **Color Temp:** 3500k, 4100k, 5000k
- **Reflector Type:** Polished Aluminum, White Aluminum, Prismatic Acrylic

